

METALFORM

MASTERS OF METAL

**EBE 75 Inward and outward opening doors and
windows | tilt and turn | in brass OT67**

METALFORM

EBE 75 Inward and outward opening doors and windows | tilt and turn | in brass OT67

Supply and installation of doors, windows, and facades, in fixed and openable sashes, for inward and outward opening doors and windows, built with thermal break profiles Secco Sistemi EBE 75.

The frame sections are made by seamlessly joining two metal shells (one whole and one external) with extruded polyamide filled with fiberglass and joined to the parts by high-density polyurethane resin. The metal shells are obtained by cold-rolling profiling strips of Copper alloy OT67 (Cu67/Zn33) with a thickness of 15/10, in accordance with the EN1652:1999 standard.

The folding unit must be kept open so that the stainless steel alignment brackets can be inserted, even in the case of continuous surface welding. The assembly of the frames is carried out by welding the internal surfaces (which can't be viewed) with the insertion of internal stainless steel reinforcement brackets and eventual brazing of the parts which are visible.

Windows Specifications:

- External and internal coplanarity profiles.
- Visible sections:
 - Fixed side node of 47 mm.

METALFORM

- Openable side node of 85 mm.
- Central node for the two panels that is asymmetrical and measures 107mm / symmetrical 145mm.
- Mandatory depth of 65 mm.
- Water, air, and wind sealing system:
 - Inward opening windows with triple mortise gasket (two sealing levels, one of which is open-joint).
 - Outward opening windows and doors with double mortise gasket (one level of closed joint gasket).
- Mobile sill for floors for doors.
- Corten steel screw-on water drains provided in the windows.
- Hot burnished stainless steel.

Doors Specifications:

- Internal and external profile complanarity.
- Visible sections:
 - Fixed 47 mm side node.
 - Opening side node of 109 mm.
 - Central node for the two wings 156 mm.
- Mandatory depth of 65 mm.
- Water, air, and wind sealing system:
 - Double mortise gasket for doors (one level of closed joint gasket).
- Mobile sill for floors for doors.

METALFORM

Additional Features:

- Complete with glass (insert glass type) fixed with glazing beads (select one of the following options: Squared, Gothic, Thin) in brass OT67.
- Windows equipped with concealed, screw-on, hot burnished stainless steel, adjustable with three wings (Ø15 mm 180kg capacity per panel).
- Alternatively, windows have tilt and turn openings with perimeter hardware, available with either concealed hinges (130 kg load capacity) or visible hinges (Ø14 mm load 150 kg capacity), the hardware equipped with an appropriate number of locking points depending on the sash size.
- Doors equipped with locks with an appropriate number of locking points proportioned with the height of the sashes and adjustable screw-on stainless steel hinges for load capacities up to 250 kg (Ø21.5 mm), and for load capacities up to 160 kg (Ø22.5 mm) in hot burnished stainless steel.
- Oxidized surfaces burnished with a mechanical cleaning process with abrasive, immersion in burnishing liquid, washing, and protection with Vaseline oil or a wax of your choice.
- Handles available in different shapes, materials, and finishes, including Brass OT67.

METALFORM

MASTERS OF METAL

UNITED KINGDOM

METALFORM

NORWAYMETAL LTD

53 Chelsea Manor Street

London, SW3 5RZ

SALES@METALFORM.UK

+44 20 81298814

GERMANY

METALFORM GMBH

Carl-Zeiss-Ring 15A

85737 Ismaning

SALES@METALFORMGROUP.DE

+49 17663630406

NORWAY

METALFORM AS

Brochmannsveien 2

1950 Rømskog

SALG@METALFORM.NO

+47 401 62 446

METALFORMGROUP

SALES@METALFORMGROUP.COM